

Soffit Specification Sheet

General Description: Allura Fiber Cement soffit is available with both traditional and contemporary aesthetics. It is suitable for residential and light commercial applications and is available in ventilated and non-ventilated designs.

Style	Finish	Net Free Air Space Per Lineal	Panel Size	Ventilation Slot Dimensions (Approx.)	Thickness
Cedar	Primer/Sealer	n/a n/a n/a	12" x 12' 16" x 12' 24" x 12'	n/a n/a n/a	1/4" 1/4" 1/4"
Cedar Ventilated/ Perforated	Primer/Sealer	6.9 Sq. In. 6.9 Sq. In. 6.9 Sq. In.	12" x 12' 16" x 12' 24" x 12'	3/16" diameter 3/16" diameter 3/16" diameter	1/4" 1/4" 1/4"
Smooth	Primer/Sealer	n/a n/a n/a	12" x 12' 16" x 12' 24" x 12'	n/a n/a n/a	1/4" 1/4" 1/4"
Smooth Ventilated/ Perforated	Primer/Sealer	6.9 Sq. In. 6.9 Sq. In. 6.9 Sq. In.	12" x 12' 16" x 12' 24" x 12'	3/16" diameter 3/16" diameter 3/16" diameter	1/4" 1/4" 1/4"
Porch Ceiling Panel Traditional Cedar or Smooth	Primer/Sealer	n/a	4' x 8'		1/4"

Finishes: Allura's exclusive primer is ready for field top coating with high quality, acrylic latex paint or stains. Factory pre-finishing available with paint or stain.

Surface Patterns: Traditional Cedar or smooth

Sizes: 12" (305mm), 16" (406mm), or 24" (610mm) x 12'. Porch panel 4' x 8'.

Composition: The products are manufactured using a multistep high-pressure process combining Portland cement, wood fiber, and specialty additives. Wood grains and other architectural features are pressed into the surface.

Technical Data: Allura Fiber Cement soffit is tested in accordance with the American Society for Testing and Materials.

ASTM C1186-02	Standard Specification for Flat Non-Asbestos Fiber Cement Sheets
ASTM C1185-96	Sampling and Testing Non-Asbestos Fiber Cement Flat Sheets, Roofing and Siding Shingles and Clapboards
ASTM E84	Surface Burning Characteristics of Building Materials
ASTM E136	Non-Combustible

Certifications: ICC ESR-1668, Texas Department of Insurance EC-16, Miami Dade 18-0222.08

Fire Resistance Characteristics: Allura Fiber Cement products are Class A fire rated with a Flame Spread Rating -0, Smoke developed -5, per ASTM E84, and is considered non-combustible in accordance with ASTM E136.

Warranty: Allura Fiber Cement soffit offers a 50-year limited transferable product warranty. A 15-year Colormax coating warranty is offered on pre-finished material.

Allura warrants that if used for its intended purpose and properly installed and maintained according to Allura's published installation instructions: (a) will resist damage caused by hail or termite attacks, (b) will resist rot, (c) will remain non-combustible, and (d) will be free from manufacturing defects in material and workmanship. See warranties for details and limitations.

Technical Support: Allura maintains a technical services staff to assist building professionals with questions regarding Allura siding products. Call 1 (844) 4 Allura for answers to technical or installation related questions.